



This product meets the Green Seal™ Standard for Floor-Care Products for Industrial and Institutional Use, GS-40, based on its reduced human and aquatic toxicity and reduced smog production potential.

Green Strip

Environmentally-Responsible Floor Stripper



Features

- Easily removes multiple coats of G2 Green Finish from any floor
- Phosphate-free, butyl-free and caustic-free
- Non-corrosive per DOT to offer user safety and simplified shipping
- Leaves no alkaline residue behind, simplifying rinsing and eliminating recoat problems
- High activity - over 30% for maximum cost benefits and reduced inventory
- VOC Content - 10.2%

Properties*

Type	Solvent Stripper
Form	Clear Liquid
Odor	Characteristic
Color	Colorless
Weight Per Gallon	8.76 Lbs.
pH	10.9
pH Use Dilution @ 1:4	10.4
Storage Stability.....	Min. 1 Year
Freeze/Thaw	Passes 3 Cycles
Foam Height	Moderate
Actives	>30%
Dilution Before Use	1:4

* Properties are typical and subject to usual manufacturing tolerances

Green Strip

18.9 LT Drum
Product Code: 8881FX



This product meets the Green Seal™ Standard for Floor-Care Products for Industrial and Institutional Use, GS-40, based on its reduced human and aquatic toxicity and reduced smog production potential.



Green Strip

18.9 LT Drum
Product Code: 8881FX

Green Strip

Environmentally-Responsible Floor Stripper



TRAINING

Directions

READ BEFORE USING

1. Dilute before using. Do not use on painted surfaces or wooden floors. Use cautiously for stripping linoleum, or rubber tile as stripper may cause bleaching, softening or bleeding.
2. Wipe up any spills or splashing from baseboards or painted surfaces immediately.
3. Dilute as instructed below. Stronger dilutions will not increase efficacy.

DIRECTIONS

1. Dilute with cold water as follows: 1 part stripper to 4 parts water.
2. Apply liberally to floor covering 100 square feet at a time. Be sure to leave surface VERY wet!
3. Allow to remain on floor 5 to 10 minutes. Agitate for 100% removal of old floor finish.
4. Pick up solution using a wet vac or auto-scrubber. If any finish remains (around baseboards), reapply stripping solution and agitate as necessary.
5. Rinse floor thoroughly. Allow floor to dry.
6. Apply G2 Green Finish.

NOTE: For stripping and maintaining asbestos containing tile, follow OSHA guidelines or EPA guidelines.



Environmentally preferable formula is butyl-free, caustic-free and phosphate-free. Non-corrosive per DOT to offer user safety and simplified shipping.

DISPOSAL

PRODUCT: Dispose of excess product in accordance with local, state, and federal regulations.

CONTAINER: Please recycle HDPE container.

VENTILATION

No special ventilation needed. However, use of adequate ventilation is good industrial practice.

IMPROPER USE OR APPLICATION

IMPROPER USE: May irritate eyes, skin and gastrointestinal tract. Avoid eye and skin contact.

IMPROPER APPLICATION: Under dilution may affect product performance and may increase the risk of health effects. Over dilution may leave a residue and affect product performance.

FIRST AID

EYES & SKIN: Flush with water (eyes 15 minutes). If irritation persists, seek medical attention.

INGESTION: If swallowed, give 2-3 large glasses of water. Seek medical attention.

CONTACT ALL BRANCHES

Tel: 1300 347 347

Fax: 1300 348 348

www.centralcleaning.com.au

Email: sales@centralcleaning.com.au

VICTORIA - NEW SOUTH WALES - TASMANIA

SOUTH AUSTRALIA - QUEENSLAND - WESTERN AUSTRALIA